

R1270

Server Model with Versatile Expandability



The R1270 is an Intel® Xeon® E processor 1U rack server based on Intel® C252 chipset. The R1270 has high expandability with 2 expansion slots and 1 proprietary slot in a configuration. This flexible expansion offers diverse applications in graphic, storage, and networking to meeting the demands of future expansion.

FEATURE

- Intel® Xeon® processor 1U rack server
- Single LGA1200 socket
- 4x 3.5"/2.5" Hot-swap Drive Bays support 2 x NVME or 4 x SATA/SAS
- Flexible storage combination for diverse usage
- Up to two PCIe® 4.0 slots and one PCIe® 3.0 proprietary slot to drive higher bandwidth
- ASUS ASMB10-iKVM for out-of-band management with ASPEED AST2600 controller

Target market

- Data center, front-end server
- Firewall, gateway server
- SMB print/file/mail/exchange server
- Surveillance

Versatile storage capability

The R1270 is the perfect choice for an operating system or application drive, making the server work as fast as possible. Four 3.5" or 2.5" hot-swap drives on front panel and one M.2 to enable extensive storage.

PCIe4.0 Ready

The R1270 is PCIe4.0 ready to support a diverse array of graphics, storage, and networking – enabling flexible scalability for demanding or increasing workloads.

Server-grade connectivity

Featuring dual onboard LAN ported by Intel I210-AT Ethernet Controller, the R1270 provides server-grade connectivity and supports high-density, high-bandwidth, low-latency access-layer networks to ensure faster transfers of large-size files used in data-intensive applications.



1. 1 x Slim type ODD (optional)
2. 4 x 3.5"/2.5" Hot-swap HDD Bays
3. 2 x USB 3.0 port
4. 1 x VGA output
5. Single 350W 80 PLUS Gold/ 1+1 450W 80 PLUS PLATINUM PSU
6. 4 x DDR4 3200/2933/2666 ECC and non-ECC UDIMM
7. 2 x Intel® I210-AT
8. Intel® LGA1200 CPU socket
9. 1 x PCIe16 (Gen4 x16 link)
10. 1 x PCIe8 (Gen4 x8 link)
11. 1 x Proprietary slot (Gen3 x4 link)
12. 1 x M.2 (up to 2280, PCIe Gen3 x4)

Contact Information: sales@equuscs.com

866.641.1475

© 2022 Equus® Compute Solutions, Inc. All Rights Reserved.

Specifications:

Processor Support		1 x Socket LGA 1200 Intel® Xeon® E processors (up to 95W) Intel® Pentium™ processors
Core Logic		Intel® C252 PCH
Memory	Total Slots Capacity Memory Type Memory Size	4 (2-channel) Maximum up to 128GB DDR4 3200/2933/2666 ECC and non-ECC UDIMM *Refer to ASUS server AVL for the latest update 32GB, 16GB, 8GB, 4GB (UDIMM) *Refer to ASUS server AVL for the latest update
Expansion Slots	Total PCI/PCI-X/PCI-E/PIKE Slots Slot Type	3 1 x PCI-E x16 (Gen4 x16 Link, switch to x8 link when slot B occupied), FH/HL 1 x PCI-E x8 (Gen4 x8 Link), HH/HL 1 x PCI-E x8 (Gen3 x4 Link), Proprietary R/A slot (optional for Intel X710 10G LAN card)
Disk Controller	SATA Controller	Intel® C252 Chipset 6 x SATA3 6Gb/s ports Intel®VROC (For Linux/Windows) (Support Software RAID 0/1/5/10)
	SAS Controller	Broadcom 9361-4i 4-port SAS 12G HW RAID card (Optional)
Storage Bays	I = internal A or S will be hot-swappable	4 x 3.5"/2.5" Hot-Swap HDD Bays, up to (2*SATA/SAS/NVMe+ 2*SATA/SAS) *SAS support only from optional SAS HBA/RAID card *NVMe support only from optional NVMe upgrade kit
Networking	LAN	2 x Intel® I210-AT + 1 x MgmtLAN
Graphic	VGA	AspeedAST2600 with 64MB VRAM
I/O Ports		Rear I/O Ports: 2 x USB 3.2 Gen 2 ports 1 x VGA port* 1 x HDMI port from CPU 1 x COM port 2 x RJ-45 ports 1 x RJ-45 ports (One for ASMB10-iKVM) Front I/O Ports: 1 x VGA port* 2 x USB 3.2 Gen1 ports *Must support by ASMB10
Switch/LED		Rear Switch/LED: 1 x Q-Code/Port 80 LED 1 x Power switch Front Switch/LED: 1 x Power switch/LED 1 x Location switch/LED 1 x Reset switch 1 x HDD Access LED 1 x Message LED LAN 1-2 LED
OS Support		Please find the latest OS Support From https://www.asus.com/event/Server/OS_support_list/OS.html
Management Solution	Software Out of Band Remote Management	ASUS Control Center (Classic) ASMB10-iKVM for KVM-over-Internet
Dimension		497mm x 439.5mm x 44mm (1U)
Net Weight Kg (CPU, DRAM & HDD not included)		10.3 kg (redundant PS) 8.47 kg (single PS)
Gross Weight Kg (CPU, DRAM & HDD not included, Packing included)		15.3 kg (redundant PS) 13.47 kg (single PS)
Power Supply		Single 350W 80 PLUS Gold PSU OR 1+1 450W 80 PLUS PLATINUM RPSU
Environment		Operation temperature: 10°C ~ 35°C Non-operation temperature: -40°C ~ 70°C Non-operation humidity: 20% ~ 90% (non-condensing)