

CloudDC A+ Server AS -1015CS-TNR



More details here

Key Applications

Web Server, Firewall Application, Data Center Optimized, Value IaaS, Cloud Computing, Compact Server, DNS & Gateway Servers, Firewall Application, CDN, Edge Nodes,

Key Features

- Single 4th Generation AMD EPYC™ 9004 Series Processors;
- 12 DIMM slots up to 3TB 3DS ECC RDIMM DDR5-4800MHz ;
- 2 PCIe 5.0 x16 FHHL;
- Dual AIOM with NCSI (OCP 3.0) for networking, 1 dedicated IPMI LAN;
- 4x 3.5/2.5" hot-swap hybrid NVMe/SATA/SAS drive bays;
- 860W redundant Platinum level 100-240Vac and 200-240 Vdc power supplies;(*Full redundancy based on configuration and application load);
- 2 On-board PCIe 3.0 x2 M.2 NVMe 80mm/110mm (Boot);



Form Factor	1U Rackmount Enclosure: 437 x 43 x 650mm (17.2" x 1.7" x 25.6") Package: 605 x 197 x 878mm (23.8" x 7.8" x 34.6")
Processor	4th Gen AMD EPYC™ 9004 Series Processor Single Socket (Socket SP5) supported TDP up to W; 4 UPI (Certain CPUs with high TDP may be supported only under specific conditions. Please contact Supermicro Technical Support for additional information about specialized system optimization)
System Memory	12 DIMM slots
Drive Bays	4x 3.5" hot-swap NVMe/SATA/SAS drive bays (4x 2.5" NVMe hybrid)(4 SATA by default) 2x NVMe (PCIe Gen 3x2, Boot drive only) M-Key, 2280/22110
Expansion Slots	2 PCIe 5.0 x16 FHHL slot(s) 2 PCIe 5.0 x16 AIOM slot(s)
On-Board Devices	Chipset: System on Chip Network Connectivity: Via Slim-AIOM IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	LAN: 1 Dedicated IPMI LAN port USB: 2 USB 3.0 port(s) (2 rear) Video: 1 VGA port(s) Serial Port: 1 COM Port(s) (1 rear)


(Front View – System)



Slot	Description
1 - 2	3.5" Hot-Swap NVMe/SAS/SATA Drive Bays

*NVMe and SAS support requires additional parts in optional parts list

(Rear View – System)



Redundant 880W Platinum Level Power Supplies*

VGA Port

Serial Port
Dedicated IPMI LAN Port
2 USB Ports

Slot	Description
1	PCIe 5.0 x16 (FHHL) Slot
2	PCIe 5.0 x16 (FHHL) Slot
3	PCIe 5.0 x16 AOM Slot (NCSS)
4	PCIe 5.0 x16 AOM Slot

*Full redundancy based on configuration and application load.

System Cooling	6x 4cm heavy duty fan(s)
Power Supply	800W/860W 1U redundant power supply Dimension (W x H x L): 54.5 x 40.25 x 322 mm Output Type: Backplanes (gold finger)
System BIOS	BIOS Type: AMI 32MB SPI FLASH ROM BIOS Features: USB Keyboard support
Management	SuperDoctor® 5; Watch Dog; SUM; SPM; SSM; IPMICFG; IPMIView for Linux/ Windows
PC Health Monitoring	FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors Voltage: System temperature, Memory temperature, CPU temperature, 3.3V standby, +5V standby, +5V, +3.3V, +12V, CPU thermal trip support
Dimensions and Weight	Height: 1.7" (43 mm) Width: 17.2" (437 mm) Depth: 25.6" (650 mm) Gross Weight: 46 lbs (20.9 kg) Net Weight: 25 lbs (11.3 kg) Packaging: 7.8" (H) x 23.8" (W) x 34.6" (D) Available Color: Black front & silver body
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super H13SSW
Chassis	CSE-LA15TS-R860AWP2